

CERTIFICATE OF COMPLIANCE

Certificate Number 20150723-MH25760
Report Reference MH25760-20120929
Issue Date 2015-JULY-23

Issued to: PELICAN ROPE WORKS
1600 E MCFADDEN AVE
SANTA ANA, CA 92705


This is to certify that representative samples of LIFE SAFETY ROPE AND EQUIPMENT FOR EMERGENCY SERVICES
See Addendum

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.


Standard(s) for Safety: NFPA 1983, Standard on Life Safety Rope and Equipment for Emergency Services, 2012 Edition
ANSI Z359.1, Safety Requirements for Personal Fall Arrest Systems, Subsystems and Components, 2007 Edition

Additional Information: See the UL Online Certifications Directory at www.ul.com/database for additional information

Only those products bearing the UL Listing Mark should be considered as being covered by UL's Listing and Follow-Up Service.

The UL Listing Mark generally includes the following elements: the symbol UL in a circle:  with the word "LISTED"; a control number (may be alphanumeric) assigned by UL; and the product category name (product identifier) as indicated in the appropriate UL Directory.

Look for the UL Listing Mark on the product.



William R. Carney, Director, North American Certification Programs
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus




CERTIFICATE OF COMPLIANCE

Certificate Number 20150723-MH25760
Report Reference MH25760-20120929
Issue Date 2015-JULY-23

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Manufacturer-Supplied Eye Terminations and Vertical Lifeline Components:

| Model | Description | Minimum Breaking Strength (MBS) kN (lbf) | NFPA Rope Class | ANSI Z359.1- 2007? |
|------------|-------------------------|--|-----------------|-----------------------|
| SEW-PE-7.5 | Sewn eye with 2WP24-7.5 | 14.6 (3,293) | Escape | No |
| SEW-WT-7.5 | Sewn eye with 2WT-7.5L | 20.8 (4,671) | Escape | Yes |
| SEW-TP-7.5 | Sewn eye with 2TP-7.5T | 17.9 (4,015) | Fire Escape | No |
| SEW-TT-7.5 | Sewn eye with 2TT-7.5T | 24.6 (5,525) | Fire Escape | Yes |
| SEW-KP-7.5 | Sewn eye with 2KP-7.5K | 16.8 (3,774) | Fire Escape | No |
| SEW-KK-7.5 | Sewn eye with 2KK-7.5K | 24.5 (5,515) | Fire Escape | Yes |
| SEW-KM-12 | Sewn eye with 2WP-120 | 23.0 (5,164) | Technical | Yes |
| SEW-KM-14 | Sewn eye with 2WP-140 | 27.5 (6,176) | Technical | Yes |
| SEW-KMP-14 | Sewn eye with 2WPP-140 | 27.3 (6,139) | Technical | Yes |
| SEW-KM-16 | Sewn eye with 2WP-160 | 40.6 (9,127) | General | Yes |
| SEW-KM-20 | Sewn eye with 2WP-200 | 46.8 (10,530) | General | Yes |



William R. Carney, Director, North American Certification Programs

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus

