

CERTIFICATE OF COMPLIANCE

Certificate Number 20180730-MH25760
Report Reference MH25760-20171127
Issue Date 2018-JULY-30

Issued to: PELICAN ROPE WORKS
1600 E MCFADDEN AVE
SANTA ANA, CA 92705

**This is to certify that
representative samples of**

Life Safety Rope and Equipment for Emergency Services
and Single Anchor Lifelines
Refer to Addendum Page

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:

NFPA 1983, Standard on Life Safety Rope and Equipment
for Emergency Services, 2017 Edition
ANSI/ASSE Z359.15, Safety Requirements for Single
Anchor Lifelines and Fall Arresters for Personal Fall Arrest
Systems, 2014 Edition

Additional Information:

See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's
Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please
contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20180730-MH25760
Report Reference MH25760-20171127
Issue Date 2018-JULY-30

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Emergency Service Life Safety Rope per NFPA 1983-2017 and Single Anchor Lifelines per ANSI/ASSE Z359.15-2014, where noted, in the following models:

Model Number	Rope Designation	Diameter (mm)	NFPA Use Class	Calculated Minimum Breaking Strength (MBS) (kN)	Percent Elongation		ANSI/ASSE Z359.15-2014?
					@ 1.35 kN	@ 2.7 kN	
2WP-200	Static Master	16.0	General	49.1 (11046 lbf)	@ 1.35 kN	1.2	Yes
					@ 2.7 kN	2.9	
					@ 4.4 kN	4.6	
2WP-160	Static Master	13.5	General	44.0 (9901 lbf)	@ 1.35 kN	1.4	Yes
					@ 2.7 kN	3.0	
					@ 4.4 kN	5.2	
2WP2-160	Static Master II	12.5	General	43.6 (9809 lbf)	@ 1.35 kN	2.4	Yes
					@ 2.7 kN	4.2	
					@ 4.4 kN	6.4	
2WP-140	Static Master	11.0	Technical	34.0 (7652 lbf)	@ 1.35 kN	2.9	No
					@ 2.7 kN	5.9	
					@ 4.4 kN	9.1	
2WP-120	Static Master	10.0	Technical	27.6 (6214 lbf)	@ 1.35 kN	2.4	N/A
					@ 2.7 kN	5.4	
					@ 4.4 kN	8.1	
2WP2-140	Static Master II	11.0	Technical	31.2 (7017 lbf)	@ 1.35 kN	4.3	No
					@ 2.7 kN	7.6	
					@ 4.4 kN	10.8	
2WPP2-140	Static Master II	11.0	Technical	30.0 (6739 lbf)	@ 1.35 kN	2.2	Yes
					@ 2.7 kN	3.4	
					@ 4.4 kN	4.4	



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20180730-MH25760
Report Reference MH25760-20171127
Issue Date 2018-JULY-30

Emergency Services Escape Rope:

Model Number	Rope Designation	Diameter (mm)	Calculated Minimum Breaking Strength (MBS) (kN)	Percent Elongation		ANSI/ASSE Z359.15-2014?
				@ 1.35 kN	@ 2.7 kN	
2WP24-7.50	Escape Pro	7.5	19.9 (4463 lbf)	@ 1.35 kN	3.6	N/A
				@ 2.7 kN	7.2	
				@ 4.4 kN	10.5	
2WT-7.5L	Escape Pro	7.5	24.0 (5395 lbf)	@ 1.35 kN	1.9	N/A
				@ 2.7 kN	2.7	
				@ 4.4 kN	3.2	

Emergency Services Fire Escape Rope:

Model Number	Rope Designation	Diameter (mm)	Calculated Minimum Breaking Strength (MBS) (kN)	Percent Elongation		ANSI/ASSE Z359.15-2014?
				@ 1.35 kN	@ 2.7 kN	
2TT-7.5T	Fire Shield-T	7.5	28.2 (6345 lbf)	@ 1.35 kN	1.5	N/A
				@ 2.7 kN	1.9	
				@ 4.4 kN	2.1	
2KK-7.5K	Fire Shield-K	7.5	27.8 (6258 lbf)	@ 1.35 kN	1.6	N/A
				@ 2.7 kN	2.2	
				@ 4.4 kN	2.8	
RSS-K7.5	Fire Shield-K	7.5	27.8 (6258 lbf)	@ 1.35 kN	1.6	N/A
				@ 2.7 kN	2.2	
				@ 4.4 kN	2.8	
2TP-7.5T	Fire Shield-TP	7.5	19.0 (4282 lbf)	@ 1.35 kN	2.3	N/A
				@ 2.7 kN	3.6	
				@ 4.4 kN	5.4	

Emergency Services Throwline:

Model Number	Rope Designation	Diameter (mm)	Calculated Minimum Breaking Strength (MBS) (kN)	ANSI/ASSE Z359.15-2014?
3PN-12Y	Water Throwline	9.0	17.3 (3888 lbf)	N/A

The above ropes may be produced in any color or combination of colors.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

