

# PELICAN ROPE

The Most Trusted Name in Rope®

**PELICAN Rope** is an ISO 9001:2008 certified manufacturer of high performance synthetic and specialty rope products, rope lanyards, slings and custom rope assemblies. For over 30 years, our devotion to innovation, quality and customer service has yielded a diverse UL Certified product line designed to not only meet or exceed the standards established by the Cordage Institute, the US Military, ASTM and NFPA but more importantly, the expectations of our loyal customers in the commercial, industrial, arborist, fire and rescue, law enforcement, manufacturing and marine industries. Dependability is our hallmark; exceptional value our everyday standard.

**WARNING: READING THIS LABEL ALONE WILL NOT PROTECT YOU FROM DEATH OR INJURY. YOU COULD BE KILLED OR SERIOUSLY INJURED IF YOU DO NOT READ AND UNDERSTAND THIS LABEL BEFORE USING ROPE, YOU MUST THOROUGHLY READ AND UNDERSTAND ALL MANUFACTURER'S INSTRUCTIONS BEFORE USE. USE AND INSPECT THIS ROPE ONLY IN ACCORDANCE WITH THE MANUFACTURER'S INSTRUCTIONS. USE THIS ROPE ONLY FOR EMERGENCY SELF RESCUE. REFER TO ADDITIONAL MANUFACTURER'S INSTRUCTIONS FURNISHED WITH THIS ROPE BEFORE USE. YOU CAN CONTACT THE MANUFACTURER AT 1-800-464-7673 FOR IMPORTANT SAFETY INFORMATION.**

- User is responsible to determine suitability of a rope for specific applications.
- Inspect the rope immediately after purchase and before and after each use visually and hand inspected by a qualified person. The inspector must thoroughly feel and inspect the complete length for dents, bumps, cuts, abrasions, and other signs of damage that may have resulted from storage and handling.
- Protect rope from abrasion. Use chafe protection over rough surfaces.
- Do not expose rope to direct flame or high temperatures
- Do not expose the rope to chemicals such as acids, alkalis, oils, paints and other agents that can deteriorate rope.
- Do not exceed the working load limit or shock-load the rope or sewn eyes
- Keep the product label and user instructions in a permanent rope record after they are removed from the rope. A copy of these user instructions and inspection records should be keep with the equipment.
- Remove rope from service and destroy by cutting into three foot sections if the rope has been exposed to any of the above stated conditions or fails inspection.
- Do not use this rope if you have not been trained in its proper use. All repairs must be made only in accordance with manufacturers' instructions.

**Satisfaction Guarantee** – Pelican Rope is dedicated to customer satisfaction. If you are not completely satisfied with the performance of one of our ropes which has been properly maintained and exposed only to normal wear and tear, we will replace it guaranteed. Pelican reserves the right to inspect and test each rope returned prior to issuing a replacement or credit.

For Hardware and Wire Rope Needs Visit:



PELICAN ROPE is a proud Member of these Organizations:



# PELICAN ROPE

The Most Trusted Name in Rope®

800-464-7673

## ROPE INSPECTION LOG

Pelican Rope Part#: \_\_\_\_\_ Lot # \_\_\_\_\_

Date First Put Into Service: \_\_\_\_/\_\_\_\_/\_\_\_\_

Date	Incident #	Type of Use	Exposure	Pass/Fail	Initials

**Safe Working Load is determined by application, conditions of use and possible danger to personnel and other considerations. The Cordage Institute specifies that the Safe Work Load of a rope is determined by dividing the Minimum Tensile Strength of the rope by a safety factor of 5 to 12 for non-critical uses and 15 for life lines.**