

# CERTIFICATE OF COMPLIANCE

**Certificate Number** MH25760  
**Report Reference** MH25760-20171127  
**Issue Date** 2020-JULY-02

**Issued to:** PELICAN ROPE WORKS  
1600 E MCFADDEN AVE  
SANTA ANA, CA 92705

**This is to certify that representative samples of** Life Safety Rope and Equipment for Emergency Services and Single Anchor Lifelines  
Refer to Addendum Page


Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

**Standard(s) for Safety:** NFPA 1983, Standard on Life Safety Rope and Equipment for Emergency Services, 2017 Edition  
ANSI/ASSE Z359.15, Safety Requirements for Single Anchor Lifelines and Fall Arresters for Personal Fall Arrest Systems, 2014 Edition

**Additional Information:** See the UL Online Certifications Directory at [www.ul.com/database](http://www.ul.com/database) for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program  
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** MH25760  
**Report Reference** MH25760-20171127  
**Issue Date** 2020-JULY-02

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Emergency Service Life Safety Rope per NFPA 1983-2017 and Single Anchor Lifelines per ANSI/ASSP Z359.15-2014, where noted, in the following models:

Model Number	Rope Designation	Diameter (mm)	NFPA Use Class	Minimum Breaking Strength (MBS) (kN)	Percent Elongation		ANSI/ASSP Z359.15-2014?
					@ 1.35 kN	@ 2.7 kN	
2WP-200	Static Master	16.0	General	49.1 (11046 lbf)	@ 1.35 kN	1.2	Yes
					@ 2.7 kN	2.9	
					@ 4.4 kN	4.6	
2WP-160	Static Master	13.0	General	44.0 (9901 lbf)	@ 1.35 kN	1.4	Yes
					@ 2.7 kN	3.0	
					@ 4.4 kN	5.2	
2WP2-160	Static Master II	12.5	General	43.6 (9809 lbf)	@ 1.35 kN	2.4	Yes
					@ 2.7 kN	4.2	
					@ 4.4 kN	6.4	
1WPP-160	Static Master PRO	12.5	General	40.0 (9000 lbf)	@ 1.35 kN	1.4	Yes
					@ 2.7 kN	2.2	
					@ 4.4 kN	3.0	
2WP-140	Static Master	11.0	Technical	34.0 (7652 lbf)	@ 1.35 kN	2.9	No
					@ 2.7 kN	5.9	
					@ 4.4 kN	9.1	
2WP-120	Static Master	10.0	Technical	27.6 (6214 lbf)	@ 1.35 kN	2.4	N/A
					@ 2.7 kN	5.4	
					@ 4.4 kN	8.1	
2WP2-140	Static Master II	11.0	Technical	31.2 (7017 lbf)	@ 1.35 kN	4.3	No
					@ 2.7 kN	7.6	
					@ 4.4 kN	10.8	
2WPP2-140	Static Master PRO	11.0	Technical	30.0 (6739 lbf)	@ 1.35 kN	2.2	Yes
					@ 2.7 kN	3.4	
					@ 4.4 kN	4.4	
1WPP-140	Static Master PRO	11.0	Technical	28.0 (6300 lbf)	@ 1.35 kN	1.6	Yes
					@ 2.7 kN	2.6	
					@ 4.4 kN	3.8	



Bruce Mahrenholz, Director North American Certification Program  
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** MH25760  
**Report Reference** MH25760-20171127  
**Issue Date** 2020-JULY-02

Emergency Services Escape Rope:

Model Number	Rope Designation	Diameter (mm)	Calculated Minimum Breaking Strength (MBS) (kN)	Percent Elongation		ANSI/ASSP Z359.15-2014?
				@ 1.35 kN	@ 2.7 kN	
2WP24-7.50	Escape Pro	7.5	19.9 (4463 lbf)	@ 1.35 kN	3.6	N/A
				@ 2.7 kN	7.2	
				@ 4.4 kN	10.5	
2WT-7.5L	Escape Pro	7.5	24.0 (5395 lbf)	@ 1.35 kN	1.9	N/A
				@ 2.7 kN	2.7	
				@ 4.4 kN	3.2	


Emergency Services Fire Escape Rope:

Model Number	Rope Designation	Diameter (mm)	Calculated Minimum Breaking Strength (MBS) (kN)	Percent Elongation		ANSI/ASSP Z359.15-2014?
				@ 1.35 kN	@ 2.7 kN	
2TT-7.5T	Fire Shield-T	7.5	28.2 (6345 lbf)	@ 1.35 kN	1.5	N/A
				@ 2.7 kN	1.9	
				@ 4.4 kN	2.1	
2KK-7.5K	Fire Shield-K	7.5	27.8 (6258 lbf)	@ 1.35 kN	1.6	N/A
				@ 2.7 kN	2.2	
				@ 4.4 kN	2.8	
RSS-K7.5	Fire Shield-K	7.5	27.8 (6258 lbf)	@ 1.35 kN	1.6	N/A
				@ 2.7 kN	2.2	
				@ 4.4 kN	2.8	
2TP-7.5T	Fire Shield-TP	7.5	19.0 (4282 lbf)	@ 1.35 kN	2.3	N/A
				@ 2.7 kN	3.6	
				@ 4.4 kN	5.4	

Emergency Services Throwline:

Model Number	Rope Designation	Diameter (mm)	Calculated Minimum Breaking Strength (MBS) (kN)	ANSI/ASSP Z359.15-2014?
3PN-12Y	Water Throwline	9.0	17.3 (3888 lbf)	N/A

The above ropes may be produced in any color or combination of colors.



Bruce Mahrenholz, Director North American Certification Program  
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

